

# AGILITY EQUIPMENT USE GUIDELINES

**\*\*Please treat this equipment as gently as if it were your own \*\***

**FAILURE TO FOLLOW THESE GUIDELINES WILL RESULT IN LOSS OF EQUIPMENT USE PRIVILEGES.**

*\* Check for spiders before moving anything. Black widows are black, round, shiny, poisonous, & plentiful.*

## **A-FRAME**


- Please do not move or change height unless you have the help of at least one person.
- Three taped height settings are available, 6'3", 5'6", 5', 4.5' and 3.5'. **PLEASE DO NOT CHANGE THESE SETTINGS!**
- To change height, first lift A-frame up and toward the center. Take the clip off and re-attach another clip.
- Slowly lower the a-frame back down again.
- To move the green a-frame, Lift one side at a time and put the wheels on.
- To move the blue A-frame, use the two wheels and hand truck. Place the hand truck at the base of the a-frame. Lift the a-frame onto the hand truck. Be very careful to move slowly and not make any abrupt turns.

## **DOGWALK**

- **YOU MUST TAKE THE PINS OUT TO MOVE THE DOGWALK. DO NOT MOVE IT WITH THE PINS IN PLACE, AS YOU WILL BEND THE PINS.**
- Please do not move unless you have the help of at least one person.
- Please do not drag dogwalk across the sand.
- Pull out the metal pins of the dogwalk. Remove each plank.
- Two people should be able to lift the mid-section of the dogwalk. You do not have to take the legs off of the center section it to move it.

## **WEAVE POLES:**

- Please do **NOT** pick up the weave poles by the junction of the pole and the base.
- Please pick up the weave poles by the flat metal base only.
- You can bend the unit like a tee-pee and carry it with one hand on each side.



## TEETER


- The regulation teeters should be moved by two people.
- If you are by yourself, please remove the pin and the plank and move each piece separately.
- You can lift the plank onto the green cart to transport.
- Transport the base on the cart as well.
- Replace the plank onto its resting notch. Replace the pin, turning it to lock it in place.

## TABLES

- PLEASE DO NOT DRAG FIXED HEIGHT TABLES ACROSS THE SAND IN THE UPRIGHT POSITION.
- Please turn tables on their side and carry or use the green cart to transport.

## PIPE TUNNELS

- Remove sand bags before moving tunnels.
- Compress tunnel and put it on green cart to move.
- Alternatively, put the long (5') jump bars through the tunnel and carry (making sure to use proper lifting technique).
- PLEASE STORE TUNNELS UPRIGHT AND COMPRESSED.
- PLEASE DO NOT STORE TUNNELS WITH BOTH OPENINGS POINTED INTO THE GROUND. IT IS IMPORTANT THAT THEY ARE ABLE TO DRY OUT AFTER GETTING WET, KEEPING THEM IN THIS POSITION ENCOURAGES MOLD TO GROW AND WILL RUIN THE TUNNEL.



## CHUTES

- PLEASE CHECK TO SEE IF CHUTE IS STAKED TO THE GROUND FIRST! Stakes can be put in at the base and at the end of the chute fabric.
- Do NOT remove the stakes by pulling on the chute fabric. Please use the hammer in the cabinet to remove the stakes.
- Tuck chute fabric into barrel before moving.
- Lift barrel onto green cart to move.

## TIRE

- The tire may be moved by dragging the frame.
- The height is changed by resetting hook for the height setting.

## JUMPS

- Jumps are easily carried upside down in groups of three. Please do not throw jumps on the ground or carry in groups larger than three. You will break the jump cups off.

***PLEASE CLOSE & BUNGEE ALL THE GATES BEFORE YOU LEAVE!***